Bottom edge of sign must be installed no lower than 5 feet or higher than 8 feet from the ground.

Sign must be permanently affixed to a pole or permanent barrier or permanent wall.

The sign must be located so that it is conspicuously facing the driver that enters the facility; or at intervals along the entrance so that no entrance is farther than 25 feet from a sign if: curbs, access barriers. landscaping, or driveways do not establish a definite entrance, or the width of an entrance exceeds 35 feet.

Sign must be made of weather-resistant material; be at least 18 inches wide and 24 inches tall; and must comply with color and layout requirements of TX Occupations Code 2308.302.

Municipalities may have additional information required on the signage, but it cannot conflict with the requirements presented here. Bright red international tow symbol at least 4 inches high. May be on a separate smaller sign attached to the top of this sign.



"TOWING AND BOOTING ENFORCED." White 2-inch letters with red background.

A statement describing who may park in the facility and prohibiting all others. Red 1-inch letters with white background.

"Unauthorized vehicles will be towed or booted at owner or operator's expense."
Red 1-inch letters, white background.
Statement authorizing who may park in a parking facility is based on the requirements of the parking facility, and will vary depending on who is authorized and who is not. For example: If the parking facility requires visitors to get a permit, the sign would say "RESIDENT AND VISITOR PARKING ONLY VISITORS MUST HAVE APPROPRIATE PERMIT ALL OTHER VEHICLES PROHIBITED"

Days and hours of towing enforcement. Red 1-inch letters with white background.

Phone number answered 24 hours a day to enable owner or operator to locate a towed vehicle. White 1-inch letters with red background.

## TOWING AND BOOTING ENFORCED

RESIDENT PARKING ONLY

**ALL OTHER VEHICLES PROHIBITED** 

NAUTHORIZED VEHICLES WILL BE TOWED OR BOOTED AT OWNER'S OR

**OPERATOR'S EXPENSE** 

AT ALL TIMES AND DAYS

(512)000-0000